

**This Page Is Inserted by IFW Operations
and is not a part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification⁴ : A41B 13/02, A61F 13/16</p>	<p>A1</p>	<p>(11) International Publication Number: WO 88/ 07335 (43) International Publication Date: 6 October 1988 (06.10.88)</p>
<p>(21) International Application Number: PCT/SE88/00116 (22) International Filing Date: 9 March 1988 (09.03.88) (31) Priority Application Number: 8701208-4 (32) Priority Date: 24 March 1987 (24.03.87) (33) Priority Country: SE (71) Applicant (for all designated States except US): MÖLN- LYCKE AB [SE/SE]; S-405 03 Göteborg (SE). (72) Inventors; and (75) Inventors/Applicants (for US only) : YGGE, Birgitta [SE/ SE]; Dr. Bex gata 7B, S-413 24 Göteborg (SE). VIG- MO, Terje [SE/SE]; Friggagatan 5B, S-411 09 Göte- borg (SE). (74) Agents: HJÄRNE, Per-Urban et al.; H. Albiñns Patent- byrå AB, Box 7664, S-103 94 Stockholm (SE).</p>		<p>(81) Designated States: AT (European patent), AU, BE (Eu- ropean patent), CH (European patent), DE (Euro- pean patent), DK, FI, FR (European patent), GB (European patent), IT (European patent), JP, LU (European patent), NL (European patent), NO, SE (European patent), US. Published <i>With international search report.</i></p>

(54) Title: DEVICE FOR THE SUPPORT OF AN ABSORBENT ARTICLE

(57) Abstract

The present invention relates to a device for support-
ing an absorbent article such as an incontinence protector,
a diaper or the like. A device performed in accordance
with the invention is distinguished by comprising a strap or
belt (11) intended to be applied around the user's waist,
and by having means (12) for engagement with coating
means (10) disposed on the article, which for its support is
connectible to the strap or belt with the aid of said means.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GA	Gabon	MR	Mauritania
AU	Australia	GB	United Kingdom	MW	Malawi
BB	Barbados	HU	Hungary	NL	Netherlands
BE	Belgium	IT	Italy	NO	Norway
BG	Bulgaria	JP	Japan	RO	Romania
BR	Brazil	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	LI	Liechtenstein	SN	Senegal
CH	Switzerland	LK	Sri Lanka	SU	Soviet Union
CM	Cameroon	LJ	Luxembourg	TD	Chad
DE	Germany, Federal Republic of	MC	Monaco	TG	Togo
DK	Denmark	MG	Madagascar	US	United States of America
FI	Finland	ML	Mali		
FR	France				

DEVICE FOR THE SUPPORT OF AN ABSORBENT ARTICLE

The present invention relates to a device for supporting an absorbent article such as an incontinence protector, a diaper or the like.

Numerous types of such devices are previously known. For example, elastic textile pants are often utilized to hold diapers or the like fixed in position during use. An alternative to such pants is the so-called all-in-one diaper which is composed of a plastic backing forming together with a diaper an integral unit. In its unused state, the most common type of all-in-one diapers is principally shaped as a pair of underpants with open side seams which are joined together with adhesive tape when using the diaper so as to make it seal like a pant around the user's abdomen.

By being both easily handled and readily replaceable, the all-in-one diapers are certainly most useful in practice. Among adults suffering from incontinence however, the wide range of individual variations as to degree of incontinence and to bodily shape and size makes it almost impossible for economic and manufacturing reasons to satisfy all demands with only a limited number of diaper variants available.

Therefore, a diaper fixed in position with the aid of a separate pant would be more useful for incontinent adults. By being able to choose the appropriate size of pant independent of the type of diaper required with regard to degree of incontinence, there is provided for the user a large selection of combination possibilities from only a restricted number of pant and diaper sizes.

There is however a drawback associated with complete diaper pants in that they are difficult to put on and replace on users of a specific category such as those incontinent, institutionalized patients who are heavy, immobile and incapable of standing on their legs, and bed-ridden or contractured patients. The use of complete

pants, which have to be wrenched over the user's legs to be properly applied, naturally complicates diaper change making it a time-consuming procedure for the nursing staff and awkward for the incontinent patient.

5 The application of pants which have to be threaded on over the feet may even cause trouble to disabled persons or those with coordination problems but otherwise capable of managing on their own at home.

10 With the present invention however there is accomplished a device of the kind set forth in the introduction and which eliminates the problem associated with previously known items of this type.

15 A device performed according to the invention is primarily distinguished in that it comprises a strap or belt intended to be applied around the user's waist and which is provided with fastening means for engagement with coacting means disposed on the article, the article to be supported being affixed to the strap or belt with the aid of said coacting means.

20 In one embodiment of the invention, the strap or belt means are eyelets or loops intended to engage with the means disposed on the article in the form of hooks, catches, buttons or the like. The strap or belt may even include a knitted, crocheted, woven or molded netting.

25 In another embodiment of the invention, the strap or belt is provided with hooks, catches, buttons or the like whereas the coacting means on the article consists of one or more meshed portions, or of apertures or eyes.

30 In a further embodiment of the invention the means disposed on the article are placed at the ends of cords or ribbons extending in the longitudinal direction of the protective article.

 In a still further embodiment of the invention the strap or belt is made openable.

35 The system including a waist strap or belt which is readily connectible with a diaper affords the possibility

of selecting waist belt and diaper independently of one another. Moreover, application of the waist band, especially if openable, onto the user's body is a most simple procedure. An additional advantage is gained in that even those with
5 restricted ability of turning or bending down may easily manage to change on their own a diaper attached to a waist belt according to the present invention. The manner of performing such a diaper change will be described in the following.

10 In contrast to complete pants, a waist belt according to the present invention will generally remain unsoiled when worn and may be used several times before it needs washing. Of course, waist belts intended to be discarded when soiled are also conceivable.

15 A device according to the invention will be described in more detail below with reference to the exemplary embodiments illustrated in the accompanying drawings, of which

Fig. 1 is a plan view of a diaper provided with the inventive attachment means;

20 Figs. 2, 3 and 4 show various embodiments of the inventive waist belt intended for use in combination with the diaper illustrated in Fig. 1;

Fig. 5 is a plan view of a diaper provided with attachment means according to another embodiment of the
25 invention;

Fig. 6 shows a waist belt intended for use in combination with the diaper illustrated in Fig. 5;

Fig. 7 is another plan view of a diaper provided with attachment means according to a still further embodiment of the invention; and
30

Fig. 8 shows the appearance of the diaper illustrated in Fig. 7 during use, together with a waist belt.

The diaper shown in Fig. 1 is of a conventional type comprising a liquid permeable inner layer 2, a liquid
35 impermeable outer layer 3, and enclosed therebetween an absorbent body 4.

The diaper 1 has the shape of a T and is intended to be worn with the cross beam 5 of the T applied to fit snugly over the user's belly (see Fig. 4).

5 Bands 8, 9 provided with hooks are disposed at either transverse end 6, 7 of the diaper, which bands 8, 9 can be made of plastics or textile. The bands 8, 9 shown in Figs. 1 and 4 are plastic bands provided with punched-out hooks 10. Instead of such punched-out hooks 10, it would of course also be possible to utilize some form of detached
10 hooks 10 which are glued or otherwise secured to the bands 8, 9.

The diaper 1 shown in Fig. 1 is intended for use together with a waist belt having eyelets or apertures for engagement with the hooks. Examples of such waist belts
15 are shown in Figs. 2 and 3. The waist belt 11 of Fig. 2 is a plastic belt with punched holes 12, whereas the waist belt 13 of Fig. 3 is made in the form of an elastic netting with relatively widely spaced meshes for engagement with the hooks of the diaper. In order to facilitate application,
20 the waist belt can be opened and closed with the aid of fastening means 14, 15 which in the exemplary embodiment are Velcro type closures. Other types of attachment means are naturally also conceivable such as belt buckles, buttons or snap fasteners, for example.

25 A waist belt 16 can be made wide enough, as in Fig. 4, to overlap the diaper 1 during use for holding it tightly pressed against the wearer's body. In this manner the diaper will remain more securely in position reducing thereby the risk of leakage past the diaper edges. With a wider waist
30 belt 16, however, additional points of attachment 17, 18 may be required between the diaper and the waist belt. In the exemplary embodiment, such points of attachment 17, 18 are arranged at the groin region of the wearer.

35 The diaper 19 shown in Fig. 5 is similar to that of Fig. 1 with the exception however that the belt portions 22, 23 disposed at the short sides are formed as a compara-

tively coarse-meshed netting. Such a diaper 19 is used in combination with a waist belt 24 provided with hooks or catches, i.e. of the type shown in Fig. 6 constituting a plastic belt with punched-out hooks 25.

5 The diaper 26 of Fig. 7, which is in all essentials similar to the diapers 1, 19 shown in Figs. 1 and 5, has two longitudinally extending elastic ribbons 27, 28. The elastic ribbons 27, 28 end at the short sides 29, 30 of the
10 diaper 26 into four loops 31-34 intended to engage with hooks or buttons 36-39 disposed on a waist belt 35 as shown in Fig. 8. The elasticity of the ribbons 27, 28 renders the
15 diaper 26 extremely pliable and well-adapted to the movements of the wearer's body during use, which makes it pleasant and comfortable to wear. Furthermore, leakage is
20 prevented to a high degree due to the elastic ribbons 27, 28 constantly holding the diaper 26 tightly against the user's body while simultaneously forming elastic leg
linings sealing around the user's thighs. There are shown in Fig. 7 merely four hooks 36-39, although the waist belt
25 35 could of course to advantage be provided with additional hooks to ascertain that the orientation of the ribbons 27, 28 in their applied state coincides in all essentials with the longitudinal direction of the diaper 26, as indicated in Fig. 7.

25 In order to further enhance the security against leakage and to achieve a soft, upholstered leg lining, the diaper 26 could be provided, as indicated in Fig. 9, with small, detached absorbent pads 40, 41 located at either
30 side of the absorbent body 42. The elastic ribbons 27, 28 extend through the diaper crotch portion in grooves 43, 44 disposed between the absorbent body 42 and the small, detached absorbent pads 40, 41.

35 To advantage, the application of a diaper and the inventive waist belt onto a user's body takes place in the following manner: The waist belt is applied around the user's waist whereafter the rear end of the diaper is

affixed to the forward portion of the waist belt. The belt is then rotated around the user's waist until the diaper has moved halfway around and is left suspended behind the user's back.

5 The forward free end of the diaper is finally brought up from between the user's legs and is attached to the waist belt across the user's belly. Since all twisting or bending movements of the body can be avoided throughout the procedure, even persons with disabled backs and legs would be able to
10 put on and change diapers without help.

 The diapers and waist belts described in the foregoing can be considered as merely exemplifying some embodiments of the inventive concept. Other fastening means such as, for example, Velcro tape of the like could be used as
15 well.

 A plurality of further modifications are conceivable within the scope of the patent claims.

CLAIMS

1. A device for supporting an absorbent article such as an incontinence protector, a diaper or the like, characterized by comprising a strap or belt (11,13;24;35) intended to be applied around the user's waist and being provided with means (12;25;36-39) for engagement with coating means (10;22;31-34) disposed on the article (1;19;26), which article for its support is affixed to the waist strap or belt with the aid of said coating means.
2. A device according to Claim 1, characterized in that the coating means (10,17, 18 and 12; 25 and 22; 23; 36-39 and 31-34) constitute hook members (10, 17, 18; 25; 36-39) and apertures or eyes (12; 22, 23; 31-34), respectively.
3. A device according to Claim 2, characterized in that at least either the waist belt (11, 13; 24; 35) or the article (1; 19; 26) comprises longitudinally and transversely extending portions and is provided with several rows of either hook members or apertures, said rows being oriented in parallel with the transverse direction of the article in its applied state.
4. A device according to Claim 3, characterized in that the perforated portions are formed of knitted, crocheted, woven or molded nettings, and that the hook members (10; 25; 36-39) are hooks, catches, buttons or the like.
5. A device according to Claim 2, characterized in that the hook members (25; 36-39) are disposed on the waist belt (24, 35).
6. A device according to Claim 2, characterized in that the hook members (10) are disposed on the article (1).
7. A device according to Claim 2, characterized in that any one of said types of coating means (31-34 or 36-39) is applied to the ends of cords or ribbons (27,28) disposed on the article and extending substantially in the longitudinal direction of the article (26).

8. A device according to Claim 2, characterized in that any one of said types of coating means is affixed to one end of cords or ribbons which have their other end affixed to the article or the waist belt, said ribbons
5 extending between the two end edges of the article and the waist belt.

9. A device according to Claim 7 or 8, characterized in that the cords or ribbons are elastic.

10. A device according to any one of the preceding claims, characterized in that the waist strap or belt (11) is openable (14).

1/4




FIG. 1




FIG. 2




FIG. 3




FIG. 4

2/4




FIG. 5




FIG. 6

3/4




FIG. 7




FIG. 8




FIG.9

INTERNATIONAL SEARCH REPORT

International Application No. PCT/SE88/00116

I. CLASSIFICATION F SUBJECT MATTER (if several classification symbols apply, indicate all) * According to International Patent Classification (IPC) or to both National Classification and IPC 4 <div style="text-align: center; padding: 5px;">A 41 B 13/02, A 61 F 13/16</div>											
II. FIELDS SEARCHED <div style="text-align: center; padding: 5px;">Minimum Documentation Searched ?</div> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th style="width: 30%; padding: 5px;">Classification System</th> <th style="padding: 5px;">Classification Symbols</th> </tr> <tr> <td style="padding: 5px;">IPC 4</td> <td style="padding: 5px;">A 41 B 13/02; A 61 F 13/16</td> </tr> <tr> <td style="padding: 5px;">US C1</td> <td style="padding: 5px;">128:284, 287-290; 604:358-402</td> </tr> </table> <div style="text-align: center; padding: 5px;">Documentation Searched other than Minimum Documentation to the Extent that such Documents are included in the Fields Searched *</div> <div style="padding: 10px; text-align: center;">SE, NO, DK, FI classes as above</div>			Classification System	Classification Symbols	IPC 4	A 41 B 13/02; A 61 F 13/16	US C1	128:284, 287-290; 604:358-402			
Classification System	Classification Symbols										
IPC 4	A 41 B 13/02; A 61 F 13/16										
US C1	128:284, 287-290; 604:358-402										
III. DOCUMENTS CONSIDERED TO BE RELEVANT* <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th style="width: 10%; padding: 5px;">Category *</th> <th style="width: 70%; padding: 5px;">Citation of Document, ** with indication, where appropriate, of the relevant passages 12</th> <th style="width: 20%; padding: 5px;">Relevant to Claim No. 13</th> </tr> <tr> <td style="text-align: center; vertical-align: top; padding: 5px;">X</td> <td style="padding: 5px;">US, A, 3 441 025 (H J RALPH) 29 April 1969 & US, E, 28483</td> <td style="text-align: center; vertical-align: top; padding: 5px;">1-10</td> </tr> <tr> <td style="text-align: center; vertical-align: top; padding: 5px;">A</td> <td style="padding: 5px;">US, A, 4 560 381 (SOUTHWELL) 24 December 1985</td> <td style="text-align: center; vertical-align: top; padding: 5px;">1, 4, 9, 10</td> </tr> </table>			Category *	Citation of Document, ** with indication, where appropriate, of the relevant passages 12	Relevant to Claim No. 13	X	US, A, 3 441 025 (H J RALPH) 29 April 1969 & US, E, 28483	1-10	A	US, A, 4 560 381 (SOUTHWELL) 24 December 1985	1, 4, 9, 10
Category *	Citation of Document, ** with indication, where appropriate, of the relevant passages 12	Relevant to Claim No. 13									
X	US, A, 3 441 025 (H J RALPH) 29 April 1969 & US, E, 28483	1-10									
A	US, A, 4 560 381 (SOUTHWELL) 24 December 1985	1, 4, 9, 10									
<div style="display: flex; justify-content: space-between;"> <div style="width: 45%;"> <p>* Special categories of cited documents: 18</p> <p>"A" document defining the general state of the art which is not considered to be of particular relevance</p> <p>"E" earlier document but published on or after the international filing date</p> <p>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> <p>"P" document published prior to the international filing date but later than the priority date claimed</p> </div> <div style="width: 45%;"> <p>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step</p> <p>"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.</p> <p>"A" document member of the same patent family</p> </div> </div>											
IV. CERTIFICATION <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%; padding: 5px;"> Date of the Actual Completion of the International Search <div style="text-align: center;">1988-06-09</div> </td> <td style="width: 50%; padding: 5px;"> Date of Mailing of this International Search Report <div style="text-align: center;">1988-06-14</div> </td> </tr> <tr> <td style="padding: 5px;"> International Searching Authority <div style="text-align: center;">Swedish Patent Office</div> </td> <td style="padding: 5px;"> Signature of Authorized Officer <div style="text-align: center;">Leif Karnsäter</div> </td> </tr> </table>			Date of the Actual Completion of the International Search <div style="text-align: center;">1988-06-09</div>	Date of Mailing of this International Search Report <div style="text-align: center;">1988-06-14</div>	International Searching Authority <div style="text-align: center;">Swedish Patent Office</div>	Signature of Authorized Officer <div style="text-align: center;">Leif Karnsäter</div>					
Date of the Actual Completion of the International Search <div style="text-align: center;">1988-06-09</div>	Date of Mailing of this International Search Report <div style="text-align: center;">1988-06-14</div>										
International Searching Authority <div style="text-align: center;">Swedish Patent Office</div>	Signature of Authorized Officer <div style="text-align: center;">Leif Karnsäter</div>										